

ducting express

REF: AS 213 PN Cloth Tape

DESCRIP: A strong and durable tape suitable for all purposes, uses and surfaces, ideal for daily urgent repairs.

FEATURES: Can be used on multiple surfaces, easy tear, high tensile, and no residual.

SPEC:	<u>Backing:</u>	PE laminated synthetic cloth
	<u>Adhesive:</u>	Synthetic rubber/resins clear adhesive
	<u>Total Weight:</u>	110 g/m ² (±10%)
	<u>Total Thickness:</u>	140 µm (±10%)
	<u>MD tensile strength:</u>	>28 N/cm
	<u>MD elongation at break:</u>	>10%
	<u>Adhesion to steel plate:</u>	>5.5 N/cm
	<u>Rolling Ball tack:</u>	<0.5

STORAGE: Store in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; ranging from 15 to 25°C with max. relative humidity of 60%. With a storage temperature lower than 10°C it is always suggested temperature reconditioning of the tape at room temperature (15°C-25°C) before its use. Shelf Life – 12 months for slit rolls and 6 for jumbo rolls (no yellowing and <10% loss in performance at 23°C, 50% humidity).

APPLICATION: Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.