

WYREFLEX

DOUBLE PLY NEOPRENE COATED DUCTING



CONSTRUCTION

Double ply Neoprene coated Polyester Fabric complete with twin wire helix.

COLOUR:

Black with yellow identification strip, 76mm diameter and above.

STANDARD LENGTH:

4 Metres.

TEMPERATURE RANGE:

-55°C to +130°C.

APPLICATIONS:

Suction and conveyance of air, fumes and gases. Dust collection and light materials handling.

PROPERTIES:

Excellent flexibility permits a tight bend radius without kinking.

OPTIONS:

Cuffed Ends.

8 metre lengths.

Technical Data

Diameter mm	Weight Kg/m	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
25	0.30	45	0.70	0.35
32	0.40	45	0.70	0.30
38	0.40	45	0.70	0.30
44	0.40	60	0.65	0.30
51	0.50	60	0.65	0.30
57	0.60	70	0.60	0.25
64	0.70	70	0.60	0.25
70	0.70	95	0.60	0.20
76	0.70	95	0.50	0.20
83	0.90	110	0.50	0.20
89	0.90	110	0.50	0.20
102	1.30	120	0.50	0.15
114	1.50	120	0.45	0.15
127	1.70	145	0.45	0.10
140	1.90	175	0.45	0.10
152	2.10	175	0.35	0.10
178	2.40	220	0.35	0.05
203	3.20	240	0.30	0.05
229	3.60	270	0.20	0.05
254	4.40	290	0.20	0.05
305	6.40	340	0.10	0.02

Technical data at + 20°C.

Other diameters/lengths available upon request.