

# ducting express

## Male connection piece



## Description


NS – coupling without gasket, used for joining SPR ducts.

### Example identification

Product code: NS - aaa

type \_\_\_\_\_  
Ød \_\_\_\_\_

## Dimensions



| Ød<br>rated [mm] | L<br>[mm] | weight<br>[kg] |
|------------------|-----------|----------------|
| 80               | 8         | 0,10           |
| 100              | 8         | 0,12           |
| 125              | 8         | 0,15           |
| 140              | 8         | 0,17           |
| 150              | 8         | 0,18           |
| 160              | 8         | 0,19           |
| 180              | 8         | 0,21           |
| 200              | 8         | 0,24           |
| 224              | 8         | 0,27           |
| 250              | 8         | 0,30           |
| 280              | 8         | 0,35           |
| 300              | 8         | 0,36           |
| 315              | 8         | 0,38           |
| 355              | 8         | 0,58           |
| 400              | 8         | 0,65           |
| 450              | 8         | 0,95           |
| 500              | 8         | 1,05           |
| 560              | 8         | 1,45           |
| 600              | 8         | 1,55           |
| 630              | 8         | 1,60           |
| 710              | 10        | 2,75           |
| 800              | 10        | 2,10           |
| 900              | 12        | 3,45           |
| 1000             | 12        | 5,70           |
| 1120             | 12        | 6,40           |
| 1250             | 12        | 7,15           |
| 1400             | 12        | 4,75           |
| 1500             | 12        | 5,10           |
| 1600             | 12        | 5,40           |