



Soft sleeve for EVA hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids

- good resistance to chemicals

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -20 °C to 70 °C
- short time to 80 °C

Design

- Wall: high grade soft PVC, electrically conductive $<10^6$

Delivery variants

- further diameters available on request
- black (standard)
- grey (standard)

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
grey						
32	44	40	85	0,060	32	227-0032-0000
38	44	40	85	0,070	38	227-0038-0000
50	49	41	90	0,090	50	227-0050-0000
black						
32	44	40	85	0,060	32	227-0032-0001
38	44	40	85	0,070	38	227-0038-0001
45	44	40	90	0,080	45	227-0045-0001
50	49	41	90	0,090	50	227-0050-0001
Electrically conductive $<10^6$; black						
32	44	40	85	0,060	32	227-0032-1003
38	44	40	85	0,070	38	227-0038-1003
50	49	41	90	0,090	50	227-0050-1003