

Standard Hanger

A versatile suspension kit for a variety of applications including the suspension of HVAC, pipework and electrical containment from different substrates.

Quick – fewer components compared to traditional methods, up to six times faster to install than traditional suspension systems


Safe – no tools or “Hot Works” permit required for installation, improving health and safety on-site

Strong – industry approved, conforms to DW144

Lightweight – easy to move and handle on-site, whilst reducing the load on the building structure

Aesthetic – the design complements enclosed and open soffit spaces



Product information / size		Product code	Length (m)	Order Quantity
	No. 1 10 kg	HF1-LG-1M	1	10
		HF1-LG-2M	2	10
		HF1-LG-3M	3	10
		HF1-LG-4M	4	10
		HF1-LG-5M	5	10
		HF1-LG-10M	10	10
	No. 2 45 kg	HF2-LG-1M	1	10
		HF2-LG-2M	2	10
		HF2-LG-3M	3	10
		HF2-LG-4M	4	10
		HF2-LG-5M	5	10
		HF2-LG-10M	10	10
	No. 3 90 kg	HF3-LG-1M	1	10
		HF3-LG-2M	2	10
		HF3-LG-3M	3	10
		HF3-LG-4M	4	10
		HF3-LG-5M	5	10
		HF3-LG-10M	10	10
	No. 4 225 kg	HF4-LG-1M	1	10
		HF4-LG-2M	2	10
		HF4-LG-3M	3	10
		HF4-LG-4M	4	10
		HF4-LG-5M	5	10
		HF4-LG-10M	10	10
	No. 5 325 kg	HF5-LG-1M	1	10
HF5-LG-2M		2	10	
HF5-LG-3M		3	10	
HF5-LG-4M		4	10	
HF5-LG-5M		5	10	
HF5-LG-10M		10	10	